



ULB-362 Series Underwater Locator Beacon



ULB-362B

SPECIFICATIONS

Operating Frequency: 27, 37.5, 45kHz
(+/- 1kHz)

Acoustic Output: 160.5dB re 1 μ Pa @ 1m

Range: 1 to 2km Based on SeaStaActivation:
Water Switch or Other Options

Power Source: Lithium Battery with a
6 Year Shelf Life

Battery Life: 30 Days

Operating Depth: 20,000ft (6,096m)

Housing Material: Aluminum

Housing Dimensions: Length - 4.00in (10.16cm)
Diameter - 1.3in (3.30cm)

Weight - ULB-362: 5.95oz (168g) max

Weight - ULB-362PL: 7.00oz (198g) max

Specifications are subject to change without notice

- ◆ **Compact size**
- ◆ **For use on ROVs, AUVs, ordnance and equipment recoveries**
- ◆ **Battery has 6 year shelf life**
- ◆ **Power Loss option available**

The **ULB-362B** is a compact, cost-effective, full ocean depth underwater locator beacon designed for applications where size is critical. Typical applications include use on ROVs, AUVs, ordnance and equipment recoveries.

The ULB-362B can withstand very high levels of vibration, pressure, and temperature. It is powered by a battery with a 6 year shelf life which provides a minimum operating life of 30 days when activated.

The **ULB-362PL/B37** is an emergency locator beacon with activation by power loss through an external connector. Ideal for ROVs and AUVs, the ULB-362PL/B37 automatically activates when a relay closes on the vehicle due to loss of power.

A water-activated switch prevents the pinger from turning on at the surface when the vehicle is shut down. No other power loss pinger is smaller, more durable, goes deeper and is backed by the service and support of RJE International, Inc.



ULB-362 PL

RJE International, Inc.

15375 Barranca Parkway, Suite I-112, Irvine, CA 92618
949-727-9399 | Sales@RJEInt.com | RJEInt.com