



## Unique features

- ▶ The only floating GMDSS radio in the market
- ▶ Intuitive and user friendly design
- ▶ Full duplex channels accessed with rechargeable battery
- ▶ Preset emergency mode when connected to primary battery
- ▶ Excellent microphone noise cancelling
- ▶ Excellent sound quality under all conditions
- ▶ Waterproof accessories

# Tron TR30 GMDSS and Maritime VHF Radio



[jotron.com](http://jotron.com)

## ➤ Tron TR30 GMDSS and Maritime VHF Radio

Tron TR30 GMDSS and Maritime VHF Radio is an innovated "two-in-one" radio, which gives the user the opportunity to access both standard GMDSS simplex channels and full maritime duplex channels. In addition, the floating Tron TR30 GMDSS and Maritime VHF Radio can be connected to an IP67 speaker microphone or a headset with a PTT-module. The small and compact two-positioning charger is easy to install and allows the user to access vital information on the display while charging. Tron TR30 GMDSS and Maritime VHF Radio has the ultimate functional design. Every detail has been developed based on user functionality, both in an emergency situation (emergency battery) and in general on board communications (rechargeable battery). When connecting the emergency battery, the radio is automatically in preset emergency mode. Only emergency required features are accessible, thus reducing critical radio adjustment time for the user.

### Tron TR30 GMDSS and Maritime radio (Part No. 87950)



### Tron TR30 GMDSS radio (Part No. 83446)



#### SPECIFICATIONS

TECHNICAL	Emergency battery (non chargeable)	Rechargeable battery
Frequency range:	TX: 154-RX 161.875MHz	TX: 154-RX:161.875MHz
Channel spacing:	25 KHz	25 KHz
Operating temperature range:	-20 to +55	-20 to +55
Battery operating time:	12 h (10-10-80)	Typ. 12 h (5-5-90) medium power
Size, WHD:	61 mm x 157 mm x 40 mm (Depth with belt clip 47 mm)	61 mm x 157 mm x 40 mm (Depth with belt clip 47 mm)
Full buoyancy:	Yes	Yes
Weight:	Approx.: 300 g	Approx.: 295 g
<b>Receiver</b>		
Maximum usable sensitivity:	< 1µV for 20dB SINAD	< 1µV for 20dB SINAD
Adjacent channel rejection:	> 70dB	> 70dB
Blocking:	> 90dB	> 90dB
Spurious response:	> 70dB	> 70dB
Harmonic distortion:	< 5%	< 5%
Intermodulation rejection:	> 68dB	> 68dB
Channel monitoring:	DW	DW/TW/Scan
<b>Transmitter</b>		
Transmitter output power (fully charged battery):	Lo: 1W , Hi 2W	Lo: 1W, Med: 2W (default), Hi: 4W
Harmonics and spurious:	< 0.25µW	< 0.25µW
Frequency error:	< +1.5kHz	< +1.5kHz
Adjacent channel power:	< -70dBc	< -70dBc
<b>Approval standards</b>		
EMC / Environmental:	IEC60945 / 301843-2	IEC60945 / 301843-2
VHF:	IEC61097-12 / EN300225	ETS301178

#### Charger

Operating power source:	12-24 DC, or 15/ 20 VAC from a 115-240VAC
Mounting:	Wall and table mountable
Size, WHD:	92 mm x 68 mm x 115 mm

#### Emergency battery

Chemical system:	Lithium/Iron Disulfide (Li/FeS <sub>2</sub> )
Voltage:	6V
Capacity:	2900 mAh

#### Rechargeable battery

Chemical system:	Lithium Polymer Battery
Voltage:	7.4V Nom
Capacity:	1550 mAh

Approved according to:



Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

VH

[jotron.com](http://jotron.com)

## CONTACT INFORMATION

Jotron AS  
P.O.Box 54  
3281 Tjodalynng  
Norway  
Tel: +47 33 13 97 00  
Fax: +47 33 12 67 80  
sales@jotron.com

Jotron UK Ltd.  
Crosland Park  
Cramlington  
NE23 1LA  
United Kingdom  
Tel: +44 (0) 1670 712000  
Fax: +44 (0) 1670 590265  
sales@jotron.com

Jotron Asia Pte. Ltd.  
19 Loyang Way  
Changi Logistics Centre  
Rear Office Block 04-26  
Singapore 508724  
Tel: +65 65426350  
Fax: +65 65429415  
sales@jotron.com

Jotron USA, Inc.  
10645 Richmond Avenue, Suite 170  
Houston, TX 77042  
USA  
Tel: +1 713 268 1061  
Fax: +1 713 268 1062  
sales@jotron.com