

MEASURE MORE,
DEPLOY LONGER,
DOWNLOAD
FASTER

MULTI-CHANNEL LOGGER (3-5)



The RBRconcerto³ multi-channel logger supports numerous sensors, offers flexible measurement schedules, standard sampling up to 2Hz, optionally up to 32Hz, large memory, ample power for extended deployments, USB-C download for large data sets, and twist activation.

FEATURES



Wi-Fi
ready



Twist activation



240M
readings



Up to 32Hz
sampling



USB-C
download



Realtime
communications

The RBRconcerto³ can be equipped with any five channel combinations. Examples:

- ▶ RBRconcerto³ C.T.Tu moored instrument; measures conductivity, temperature, and turbidity
- ▶ RBRconcerto³ C.T.D.Tu moored instrument; measures conductivity, temperature, depth, and turbidity
- ▶ RBRconcerto³ C.T.D.Tu|fast8 turbidity, 8Hz profiling instrument; fast sensor response
- ▶ RBRconcerto³ C.T.D|fast16 16Hz profiling instrument; fast sensor response
- ▶ RBRconcerto³ C.T.D|fast32 32Hz profiling instrument; fast sensor response

Custom configurations can include up to 5 of the following options:

- ▶ Temperature
- ▶ Depth
- ▶ Conductivity
- ▶ pCO₂
- ▶ Tides
- ▶ Waves
- ▶ Dissolved O₂
- ▶ pCH₄
- ▶ Turbidity
- ▶ Fluorescence
- ▶ Transmission
- ▶ Nitrate
- ▶ pH
- ▶ ORP (RedOx)
- ▶ PAR
- ▶ Irradiance

MULTI-CHANNEL LOGGER (3-5)

MEASURE MORE, DEPLOY LONGER, DOWNLOAD FASTER

RBRconcerto³ loggers make it easy to configure the optimum sampling regime for your measurements. The large data storage capacity, and fast download ability facilitate long deployments with higher sampling rates. The RBRconcerto³ is also available in an extended body that has more battery power for longer deployments or to support additional sensors configurations. Almost any sensor from RBR can be interfaced to the RBRconcerto³. Dataset export to Matlab, Excel, OceanDataView®, or text files makes post processing with your own algorithms effortless.

Specifications

Physical

Storage:	240M readings
Power:	8 AA cells
External power:	4.5-30 VDC
Communication:	USB-C or RS-232/485
Clock drift:	±60 seconds/year
Depth rating:	750m (plastic) 10,000m (titanium)
Housing:	Plastic or titanium
Size:	Configuration dependent
Weight:	Configuration dependent
Sampling speed:	2Hz to 24h
Fast option:	fast8 — 1 – 8Hz (profiling) fast16 — 1 – 8, 16Hz (profiling) fast32 — 1 – 8, 16, 24, 32Hz (profiling)

Conductivity (up to 6000m)

Range:	0-85mS/cm
Initial accuracy:	±0.003 mS/cm
Resolution:	0.001 mS/cm
Typical stability:	0.010 mS/cm per year

Temperature

Range:	-5°C to 35°C
Initial accuracy:	±0.002°
Resolution:	0.00005°C
Time constant:	~1s (standard), ~0.1s (option)
Typical stability:	0.002°C per year

Depth

Range:	20 / 50 / 100 / 200 / 500 / 750 1000 / 2000 / 4000 / 6000 / 10,000m (dbar)
Initial accuracy:	±0.05% FS (full scale)
Resolution:	0.001% FS
Time constant:	<0.01s
Typical stability:	0.05% FS

Options

- ▶ Wi-Fi communication
- ▶ |fast8, |fast16 or |fast32Hz sampling for profiling
- ▶ External data and power connector with USB, RS-232, or RS-485



RBR Ltd

95 Hines Road
Ottawa, Ontario
Canada K2K 2M5

+1 613 599 8900
info@rbr-global.com
rbr-global.com